



drawing for customer information

| | | | | | | |
|---|-------------|--|--|--|--|---------------------|
| FEUERHERDT EMI Shielding Products Specialist for Contact Springs | | tolerances: | length tolerance: | dimensions in mm | scale: 2:1 | revision: 00 |
| | | X,X ± 0,5 X,XX ± 0,2 X,XXX ± 0,1 | 100-300 ± 0,5 300-400 ± 0,8 400-500 ± 1 > 500 ± 1,5 | unmeasured contours according to 3D data | material: rawmaterial: CuBe 2, 1/2H finalstate: CuBe 2, 1/2HT | |
| | | date: | name: | description: | | |
| | | created 18.02.21 | Pröhl | <h1>type CL67</h1> | | |
| | | checked 18.02.21 | Akrim | | | |
| | | released | | drawing number: | | |
| | | surface code: | | <h1>PC.016.10.C</h1> | | |
| | | bright finish -02 | zink chromate/ | | | |
| | | gold -03 | clear -15 | sheet: 1 | | |
| | | silver -04 | bright tin -17 | | | |
| | | | bright nickel -19 | | | |
| rev. | description | date | name | thickness: t= 0,127 | replacement drawing: | |

Stripes can be cut off after each finger on request.
 Calculation of length in mm:
 strip length = number of fingers x 1 pitch - 1 slot

