



**DETAIL B**  
MABSTAB 20 : 1

**ANSICHT A**  
MABSTAB 10 : 1

**drawing for customer information**

<b>FEUERHERDT</b> EMI Shielding Products Specialist for Contact Springs		tolerances:	length tolerance:	dimensions in mm	scale: <b>2:1</b>	revision: <b>00</b>
		X,X ± 0,5 X,XX ± 0,2 X,XXX ± 0,1	100-300 ± 0,5 300-400 ± 0,8 400-500 ± 1 > 500 ± 1,5	unmeasured contours according to 3D data	material: <b>rawmaterial: CuBe 2, 1/2H</b> <b>finalstate: CuBe 2, 1/2HT</b>	
		date:	name:	description:		
		created 15.06.20	<b>Gutmann</b>	<b>type Z</b>		
		checked 30.07.20	<b>Pröhl</b>			
		released		drawing number:		
		surface code:		<b>TC.019.00.C</b>		
		bright finish -02 gold -03 silver -04	zink chromate/clear -15 bright tin -17 bright nickel -19			
rev.	description	date	name	thickness: t=0,127	replacement drawing:	

**Stripes can be cut off after each finger on request.**  
**Calculation of length in mm:**  
**strip length = number of fingers x 1 pitch - 1 slot**

**1**